

AXXIUM PRO

THE BEST SOLUTION™





Introducing the AXXIUM™ PRO UPS...

The Best Solution for your Expanding Network

In today's IT space, the one sure thing you can count on is change. That's why your UPS needs to be as expandable as your environment. That's why you need the new Axxium Pro.

Axxium Pro keeps your network protected and profitable by combining N+X redundancy with hot-swappable power and battery modules, all in a modular design that's scalable from 3-to-18kVA. That assures reliability.




And that makes Axxium Pro the most flexible UPS solution in the IT space – with revolutionary technology (patents pending) and a price uncommonly low.



3kVA Power Module
(1 per slot)



Battery Module
(2 per slot)



Two BestDock™
Communication Slots



FREE CheckUPS II Power
Management Software Suite

Modular N+X Power & Logic Redundancy provides the highest level of reliability in today's IT space.

Modular design is highly serviceable, with an easy-to-use, menu-driven LCD display that makes diagnostic troubleshooting easy to perform.

MODULARITY ...

Scalability is enhanced by built-in expansion slots that accommodate additional power and battery modules, as your power protection needs increase in the future.

The Key to Axxium Pro's REDUNDANCY, SCALABILITY and AFFORDABILITY

This high-frequency, transformer-less, multi-conversion UPS (3kVA-18kVA) is engineered to accommodate worldwide voltages and frequencies in 3-Slot, 6-Slot, 9-Slot and 12-Slot enclosures.

Standard on-line modes are on-battery, double-conversion, and fault bypass. A high efficiency/power-saver mode offers additional savings.

Two BestDock™ communication slots accept a variety of power management cards, including BestLink™ SNMP/WEB Adapter.

Best Power CheckUPS II Power Management Software Suite provides a complete power protection solution compatible with most major operating systems.

- Provides protection against spikes, sags, surges, noise, lightning, and power outages.
- Axxium Pro comes with a two-year limited warranty against factory or workmanship defects; plus our "Double Lifetime" limited warranty to factory-repair UPS damage from lightning strikes, and covers up to US \$25,000 for damage to connected equipment resulting from a spike or surge.



AXXIUM PRO SPECIFICATIONS

Models	0650					
Capacity (VA/Watts)	3.0/2.1	6.0/4.2	9.0/6.3	12.0/8.4	15.0/10.5	18.0/12
Dimensions (H x W x D)	17.8 x 17 x 23.9 in.					
3-Slot Cabinet	453 x 432 x 607 mm					
6-Slot Cabinet	31.5 x 17 x 23.9 inches / 800 x 432 x 607 mm					
9-Slot Cabinet	47 x 24 x 25 inches / 1194 x 610 x 635 mm					
12-Slot Cabinet	60.7 x 24 x 25 inches / 1542 x 610 x 635 mm					
Input Connection	Hardwired input standard (Optional input cords available)			Hardwired		
Output Connection	Hardwired output standard (Optional internal output distribution available)					
Typical Runtime: Full/Half Load	8-10/20-25 minutes typical (Optional internal and external runtime available)					
Battery Type	Hot-swappable, sealed, maintenance-free lead acid batteries with 3-5 year typical lifetime					
Operation						
Nominal Input Voltage	208-240VAC or 200/100, 208/120, 220/127, 220/110, 240/120					
Input Voltage Range	176-276VAC					
Input Power Factor	>0.98					
Input Current THD	<10% at 100% load					
Operating Frequency	50/60Hz (±3Hz)					
Nominal Output Voltage	208-240 or 200/100, 208/120, 220/127, 220/110, 240/120					
Output Voltage Regulation	±3% of nominal					
Output Voltage Waveform	Sine wave					
Output Voltage THD	<3% THD (linear loads)					
Overload Capacity	150% for 10 seconds, 300% for 12 cycles					
Recharge Time	<4 hours standard					
Lightning & Surge Protection	ANSI/IEEE C62.41 (1991); ANSI/IEEE C62.45 (1987) Category B. Meets IEC 61000-4-5					
Efficiency	>88%					
Safety Certification	UL, CSA (cUL), TUV					
EMC Emissions	FCC and CSPR 22 class A					
EMC Immunities	EN/IEC 61000-4-2, -3, -4, -5, and -2-2					
Other Standards	ISO9000 and Year 2000 compliant					
Communication						
LCD Display	Programmable 4 x 20 character backlit LCD, multiple languages (English, French, Spanish, German)					
Communication Slots	2 BestDock™ Slots					
Communication Port	RS-232 serial port (DB-9) plus contact closures					
SNMP Capability	Yes					
Contact Closure	Yes					
Emergency Power Off (EPO) Capability	Input for external EPO closure					
Environmental						
Operating Temperature	0 to 40°C, 32 to 104°F (derate 1°C per 300m above 1525m)					
Storage Temperature	-20 to 40°C (60°C without batteries), -4 to 104°F (140°F without batteries)					
Relative Humidity	0 - 95% non-condensing					
Audible Noise at One Meter	<50 dBA					
Altitude	3,050m (10,000 ft.) above sea level					
All specifications subject to change without notice.						



P.O. Box 280, Necedah, WI 54646 USA 1.800.356.5794 www.bestpower.com